

Screwed **BSPP** Male x Female, Nickel Plated Body, Full Bore, **Red** Aluminium Lever

Pressure / Temperature Specifications	
Pressure	PN40 ¼" to ½"
	PN32 ¾" & 1"
	PN25 1¼" to 2½"
	PN16 3" & 4"
Temperature	-20°C to 110°C

Material Specifications		
1.	Body	Nickel Plated Brass CW 617 N
2.	Body End	Nickel Plated Brass CW 617 N
3.	Ball	Chrome Plated Brass CW 617 N
4.	Seats	PTFE
5.	O-ring	NBR
6.	Stem	Brass CW 614 N
7.	Lever	Plastic Coated Steel
8.	Screw	Zinc Plated Steel

Dimensions								
Size	Ø	H	S	L	F	Kv	Cv	Kg
¼"	8	45	38	80	10.5	3.6	4.2	0.11
¾"	10	45	42	80	10.5	6.6	76.0	0.13
½"	14.5	47	48	80	13	16.5	19.1	0.17
¾"	19	53	57	90	14	25.0	29.0	0.28
1"	24	58	69	90	17	46.0	53.0	0.41
1¼"	30.5	69	79	120	17	87.0	101.0	0.64
1½"	37	81	89	135	19	140.0	162.0	0.94
2"	47	94	109	160	21	275.0	318.0	1.51

