


Media: air – water – gas – light oil – vacuum  
 Pressure range: 0 to 10 bar max  
 Media temperature: 120°C max  
 Ambient temperature: -10° to +50°C max  
 Media viscosity: 50 centistokes max  
 Mounting: any position  
 Opening / Closing time: 20 mSec Max



## 2/2 Brass

1/8 – 1/2

### NORMALLY CLOSED 2 WAY DIRECT ACTING

0 – 10 Bar

## TYPE AD612



#### PRESSURE

Ø Port BSP	Ø Orifice (mm)	Coil	Flow Kv Ltr/min	Pressure Rating (bar) ΔP			Seals	Part Number
				Min	Max AC	Max DC		
1/8	3.0	WPG1	4	0	10	7	NBR +80°C SILICONE +120°C EPDM +120°C FKM +120°C  *PTFE +120°C *VST +120°C	AD6A + seal + voltage
	4.0		5.5	0	7	5		AD6B + seal + voltage
	5.0		7.2	0	5	3.5		AD6C + seal + voltage
1/4	3.0		4	0	10	7		AD8A + seal + voltage
	4.0		5.5	0	7	5		AD8B + seal + voltage
	5.0		7.2	0	5	3.5		AD8C + seal + voltage
3/8	4.0	WPG2	5.5	0	10	7		AD10A + seal + voltage
	6.0		10.5	0	5	3.5		AD10B + seal + voltage
	8.0		16.2	0	2	1.4		AD10C + seal + voltage
1/2	6.0		10.5	0	5	3.5		AD12A + seal + voltage
	8.0		16.2	0	2	1.4		AD12B + seal + voltage

#### OPTIONS

IP68 (EN60529:1991+A1:2000) CSA + UL Approved Coil & IP65 LED Connector PG11 – DIN 43650 A  
 ATEX 22003EX Coil: ATEX EExmIIT4 II 2G & 2D IP65 T130°C (Pressure rating 70% of WPG2 DC rated coil)  
 \* PTFE, VST, CR, ECO, HNBR or Hypalon Seals  
 Silver shading ring (ADxxS)  
 Manual Over Ride (See picture above)  
 NPT Thread  
 Other custom made options available upon request

#### ELECTRICAL DATA

Voltage (-10% + 15%) Continuous duty 100%	Coil	Power Consumption		Insulation class	Enclosure	Electrical connections
		Inrush	Holding			
~ 24 - 110 - 230 (50 or 60 Hz)	WPG1	11.2VA	8.2VA	H 180°C	IP 65 with connector	3 spades DIN 43650A DIN 40050 VDE 0110
= 12 - 24 (DC)		12 Watts				
~ 24 - 110 - 230 (50 or 60 Hz)	WPG2	18.7VA	15.3VA			
= 12 - 24 (DC)		18 Watts				

#### CONSTRUCTION

Body: Brass  
 Tube and Spring: 304 Stainless/ Brass Armature: 430F Stainless Other internal parts: Stainless  
 Shading ring: copper (optional Silver)  
 Seals and gaskets: FKM (Optional EPDM, NBR, SILICONE, PTFE, VST, CR, ECO, HNBR and Hypalon)  
 Moulded coil: Resin

#### REPAIR KIT

Coil	Coil size (WPG1 or WPG2) + voltage
Armature + Seal	SP210 + Valve Part Number

#### OVERALL DIMENSIONS



Item	Part No	Description
1	SP201-*	Nut
2	SP202-*	Washer
3	SP203-*	Nameplate
5	WPG*	Coil
6	SP206-*	Gasket
7	SP207-*	Connector
9	SP209-*	Core Tube
10	SP210-*	Armature Assembly
17	SP211-*	Valve Body

\* = Valve Part Number

Model	A	B	C	F*	G	H	Kg
AD8	41	19	89	63	15	10.5	0.47
AD10	50	25	90	65	15	11.7	0.73
AD12	55	27	91	65	17	13	0.78

