

Screwed **BSPP** Male x Female, Nickel Plated Body, Full Bore, Butterfly Handle

| Pressure / Temperature Specifications | |
|---------------------------------------|----------------|
| Pressure | PN40 ¼" to ½" |
| | PN32 ¾" & 1" |
| Temperature | -20°C to 110°C |

| Material Specifications | | |
|-------------------------|----------|------------------------------|
| 1. | Body | Nickel Plated Brass CW 617 N |
| 2. | Body End | Nickel Plated Brass CW 617 N |
| 3. | Ball | Chrome Plated Brass CW 617 N |
| 4. | Seats | PTFE |
| 5. | O-ring | NBR |
| 6. | Stem | Brass CW 614 N |
| 7. | Lever | Aluminium |
| 8. | Screw | Zinc Plated Steel |

| Dimensions | | | | | | | | | |
|------------|------|----|----|----|------|------|------|------|--|
| Size | Ø | H | S | L | F | Kv | Cv | Kg | |
| ¼" | 8 | 37 | 45 | 52 | 10.5 | 3.6 | 4.2 | 0.1 | |
| ⅜" | 10 | 38 | 48 | 52 | 10.5 | 6.6 | 76.0 | 0.13 | |
| ½" | 14.5 | 41 | 55 | 52 | 13 | 16.5 | 19.1 | 0.16 | |
| ¾" | 19 | 48 | 65 | 60 | 14 | 25.0 | 29.0 | 0.26 | |
| 1" | 24 | 51 | 77 | 60 | 17 | 46.0 | 53.0 | 0.39 | |

